

Creation Date Oct-2013 Revision Date Oct-2018 Revision Number 2

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identification

Product Description: <u>Diethyl ether</u>
Product Grade: SQ, ER, HPLC

Cat No.: Q33705, Q32105, Q32107, Q33707, Q43476

Synonyms Ethyl ether; Ether

 CAS-No
 60-29-7

 EC-No.
 200-467-2

 Molecular Formula
 C4 H10 O

Reach Registration Number 01-2119535785-29

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company Thermo Fisher Scientific India Pvt. Ltd

403-404, B-wing, Delphi, Hiranandani Business Park,

Powai, Mumbai 400076, INDIA.

E-mail address <u>laboratorysolutions@thermofisher.com</u>

1.4. Emergency telephone number

India Toll Free: 18 00 22 22 30 Chemtrec US: (800)424-9300 Chemtrec EU: 001(202)483-7616

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids Category 1

Health hazards

Acute oral toxicity Category 4
Specific target organ toxicity - (single exposure) Category 3

Environmental hazards

Based on available data, the classification criteria are not met

Classification according to EU Directives 67/548/EEC or 1999/45/EC

R-phrase(s) R12 - Extremely flammable

R19 - May form explosive peroxides

R22 - Harmful if swallowed

R66 - Repeated exposure may cause skin dryness or cracking

R67 - Vapors may cause drowsiness and dizziness

For the full text of the R-phrases and H-Statements mentioned in this Section, see Section 16.

2.2. Label elements



Signal Word

Danger

Hazard Statements

H224 - Extremely flammable liquid and vapor

H302 - Harmful if swallowed

H336 - May cause drowsiness or dizziness

EUH019 - May form explosive peroxides

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P233 - Keep container tightly closed

P240 - Ground/Bond container and receiving equipment

P243 - Take precautionary measures against static discharge

P261 - Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray

P301 + P312 - IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell

P403 + P235 - Store in a well-ventilated place. Keep cool

2.3. Other hazards

No information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Component	CAS-No	EC-No.	Weight %	CLP Classification - Regulation (EC) No 1272/2008	DSD Classification - 67/548/EEC
Ethyl ether	60-29-7	EEC No. 200-467-2	>95	Acute Tox. 4 (H302) STOT SE 3 (H336) Flam. Liq. 1 (H224) (EUH019) (EUH066)	F+; R12 R19 Xn; R22 R66 R67

Reach Registration Number	01-2119535785-29
---------------------------	------------------

For the full text of the R-phrases and H-Statements mentioned in this Section, see Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Diethyl ether Revision Date Oct-2018

Obtain medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Obtain medical attention.

Ingestion Do not induce vomiting. Call a physician or Poison Control Center immediately.

Inhalation Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth

resuscitation if victim ingested or inhaled the substance; induce artificial respiration with a

respiratory medical device. Obtain medical attention.

Protection of First-aiders Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Breathing difficulties. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Cool closed containers exposed to fire with water spray.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Extremely flammable. Risk of ignition. Vapors may travel to source of ignition and flash back. Vapors may form explosive mixtures with air. Containers may explode when heated. May form explosive peroxides. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO2), peroxides.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes and clothing.

6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional ecological information.

6.3. Methods and material for containment and cleaning up

Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary measures against static discharges. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Diethyl ether Revision Date Oct-2018

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment. Handle under an inert atmosphere. Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Do not breathe vapors or spray mist. Keep away from open flames, hot surfaces and sources of ignition. If peroxide formation is suspected, do not open or move container. Use only non-sparking tools. Use explosion-proof equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

7.2. Conditions for safe storage, including any incompatibilities

Flammables area. Store under an inert atmosphere. Keep away from open flames, hot surfaces and sources of ignition. May form explosive peroxides. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep away from heat and sources of ignition. Keep container tightly closed in a dry and well-ventilated place.

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive 2006/15/EC of 7 February 2006 establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC on the protection of the health and safety of workers from the risks related to chemical agents at work. **UK** - EH40/2005 Containing the workplace exposure limits (WELs) for use with the Control of Substances Hazardous to Health Regulations (COSHH) 2002 (as amended). Updated by September 2006 official press release and October 2007 Supplement. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority.

Component	European Union	The United Kingdom	France	Belgium	Spain
Ethyl ether	TWA: 100 ppm 8 hr	STEL: 200 ppm 15 min	TWA / VME: 100 ppm (8	TWA: 100 ppm 8 uren	STEL / VLA-EC: 200
	TWA: 308 mg/m ³ 8 hr	STEL: 620 mg/m ³ 15	heures). restrictive limit	TWA: 308 mg/m ³ 8 uren	ppm (15 minutos).
	STEL: 200 ppm 15 min	min	TWA / VME: 308 mg/m ³	STEL: 200 ppm 15	STEL / VLA-EC: 616
	STEL: 616 mg/m ³ 15	TWA: 100 ppm 8 hr	(8 heures). restrictive	minuten	mg/m³ (15 minutos).
	min	TWA: 310 mg/m ³ 8 hr	limit	STEL: 616 mg/m ³ 15	TWA / VLA-ED: 100
		_	STEL / VLCT: 200 ppm.	minuten	ppm (8 horas)
			restrictive limit		TWA / VLA-ED: 308
			STEL / VLCT: 616		mg/m³ (8 horas)
			mg/m ³ . restrictive limit		

Component	Italy	Germany	Portugal	The Netherlands	Finland
Ethyl ether	TWA: 100 ppm 8 ore. TWA: 308 mg/m³ 8 ore. STEL: 200 ppm 15 minuti. Breve termine STEL: 616 mg/m³ 15 minuti. Breve termine	TWA: 400 ppm (8 Stunden). AGW - exposure factor 1 TWA: 1200 mg/m³ (8 Stunden). AGW - exposure factor 1 TWA: 400 ppm (8 Stunden). MAK TWA: 1200 mg/m³ (8 Stunden). MAK Höhepunkt: 400 ppm Höhepunkt: 1200 mg/m³	STEL: 200 ppm 15 minutos STEL: 616 mg/m³ 15 minutos TWA: 100 ppm 8 horas TWA: 308 mg/m³ 8 horas	STEL: 616 mg/m³ 15 minuten TWA: 308 mg/m³ 8 uren	TWA: 100 ppm 8 tunteina TWA: 310 mg/m³ 8 tunteina STEL: 200 ppm 15 minuutteina STEL: 620 mg/m³ 15 minuutteina

(Component	Austria	Denmark	Switzerland	Poland	Norway
	Ethyl ether	MAK-KZW: 200 ppm 15	TWA: 100 ppm 8 timer	STEL: 400 ppm 15	STEL: 600 mg/m ³ 15	TWA: 100 ppm 8 timer
	-	Minuten	TWA: 309 mg/m ³ 8 timer	Minuten	minutach	TWA: 300 mg/m ³ 8 timer

Diethyl ether Revision Date Oct-2018

MAK-KZW: 600 mg/m ³ 15 Minuten MAK-TMW: 100 ppm 8 Stunden MAK-TMW: 300 mg/m ³ 8 Stunden	STEL: 1200 mg/m ³ 15 Minuten TWA: 400 ppm 8 Stunden TWA: 1200 mg/m ³ 8 Stunden	TWA: 300 mg/m³ 8 godzinach	STEL: 150 ppm 15 minutter. STEL: 375 mg/m ³ 15 minutter.
---	---	-------------------------------	--

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Ethyl ether	TWA: 100 ppm TWA: 308 mg/m³ STEL : 200 ppm STEL : 616 mg/m³	TWA-GVI: 100 ppm 8 satima. TWA-GVI: 308 mg/m³ 8 satima. STEL-KGVI: 200 ppm 15 minutama. STEL- KGVI: 616 mg/m³ 15 minutama.	TWA: 100 ppm 8 hr. TWA: 308 mg/m ³ 8 hr. STEL: 200 ppm 15 min STEL: 616 mg/m ³ 15 min	STEL: 200 ppm STEL: 616 mg/m³ TWA: 100 ppm TWA: 308 mg/m³	TWA: 300 mg/m³ 8 hodinách. Ceiling: 600 mg/m³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Ethyl ether	TWA: 100 ppm 8 tundides. TWA: 308 mg/m³ 8 tundides. STEL: 200 ppm 15 minutites. STEL: 616 mg/m³ 15 minutites.	TWA: 100 ppm 8 hr TWA: 308 mg/m ³ 8 hr STEL: 200 ppm 15 min STEL: 616 mg/m ³ 15 min	STEL: 500 ppm STEL: 1500 mg/m³ TWA: 400 ppm TWA: 1200 mg/m³	STEL: 616 mg/m³ 15 percekben. CK TWA: 308 mg/m³ 8 órában. AK lehetséges borön keresztüli felszívódás	STEL: 200 ppm STEL: 616 mg/m ³ TWA: 100 ppm 8 klukkustundum. TWA: 308 mg/m ³ 8 klukkustundum. Ceiling: 200 ppm Ceiling: 616 mg/m ³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Ethyl ether	STEL: 200 ppm	TWA: 300 ppm IPRD	TWA: 100 ppm 8	TWA: 100 ppm	TWA: 99 ppm 8 ore
	STEL: 616 mg/m ³	TWA: 900 mg/m ³ IPRD	Stunden	TWA: 308 mg/m ³	TWA: 300 mg/m ³ 8 ore
	TWA: 100 ppm	STEL: 400 ppm	TWA: 308 mg/m ³ 8	STEL: 200 ppm 15	TWA: 100 ppm 8 ore
	TWA: 308 mg/m ³	STEL: 1200 mg/m ³	Stunden	minuti	TWA: 308 mg/m ³ 8 ore
			STEL: 200 ppm 15	STEL: 616 mg/m ³ 15	STEL: 264 ppm 15
			Minuten	minuti	minute
			STEL: 616 mg/m ³ 15		STEL: 800 mg/m ³ 15
			Minuten		minute
					STEL: 200 ppm 15
					minute
					STEL: 616 mg/m ³ 15
					minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Ethyl ether	TWA: 300 mg/m³ STEL: 900 mg/m³ vapor	Ceiling: 616 mg/m³ TWA: 100 ppm TWA: 308 mg/m³	TWA: 100 ppm 8 urah TWA: 308 mg/m³ 8 urah STEL: 200 ppm 15 minutah STEL: 616 mg/m³ 15 minutah	STV: 400 ppm 15 minuter STV: 1200 mg/m³ 15 minuter LLV: 300 ppm 8 timmar. LLV: 900 mg/m³ 8 timmar.	TWA: 100 ppm 8 saat TWA: 308 mg/m³ 8 saat STEL: 200 ppm 15 dakika STEL: 616 mg/m³ 15 dakika

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies.

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Diethyl ether Revision Date Oct-2018

Derived No Effect Level (DNEL)	No information available	;		
Route of exposure	Acute effects (local)	Acute effects (systemic)	Chronic effects (local)	Chronic effects (systemic)
Oral				
Dermal				
Inhalation				

Predicted No Effect Concentration No information available. (PNEC)

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Safety glasses with side-shields (European standard - EN 166)

Hand Protection Protective gloves

Glove material Nitrile rubber	Breakthrough time < 33 minutes	Glove thickness 0.28 - 0.35 mm	EU standard EN 374 Level 2	Glove comments Permeation rate 36 µg/cm2/min As tested under EN374-3 Determination of
Viton (R)	< 19 minutes	0.3 mm		Resistance to Permeation by Chemicals

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to

EN371

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Colorless
Physical State Liquid

Diethyl ether Revision Date Oct-2018

Odor aromatic

No data available **Odor Threshold** рΗ No information available -116 °C / -176.8 °F Melting Point/Range **Softening Point** No data available **Boiling Point/Range** 34.6 °C / 94.3 °F

Flash Point -45 °C / -49 °F Method - No information available

Evaporation Rate 37.5 (Butyl Acetate = 1.0) Liquid

Flammability (solid,gas) Not applicable

Explosion Limits Lower 1.7 vol % Upper 48 vol %

587 mbar @ 20 °C **Vapor Pressure**

Vapor Density 2.55 (Air = 1.0)

Specific Gravity / Density 0.714

Not applicable Liquid **Bulk Density**

69 g/L (20°C) Water Solubility No information available

Solubility in other solvents Partition Coefficient (n-octanol/water)

Component log Pow Ethyl ether 0.82

160 °C / 320 °F **Autoignition Temperature** No data available **Decomposition Temperature** 0.2448 cP at 20 °C Viscosity

No information available **Explosive Properties** Vapors may form explosive mixtures with air

No information available **Oxidizing Properties**

9.2. Other information

C4 H10 O **Molecular Formula Molecular Weight** 74.12

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity Yes

10.2. Chemical stability

May form explosive peroxides: Air sensitive: Light sensitive: Hygroscopic

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions May form explosive peroxides.

10.4. Conditions to avoid

Incompatible products. Heat, flames and sparks. Exposure to air. Exposure to light. Exposure to moisture. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). peroxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Product Information

(a) acute toxicity;

Oral Category 4

Diethyl ether Revision Date Oct-2018

Dermal Inhalation	Based on available data, the classification criteria are not met Based on available data, the classification criteria are not met			
Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	
Ethyl ether	1215 mg/kg (Rat)	20 mL/kg (Rabbit)		

Based on available data, the classification criteria are not met (b) skin corrosion/irritation;

(c) serious eye damage/irritation; Based on available data, the classification criteria are not met

(d) respiratory or skin sensitization;

Based on available data, the classification criteria are not met Respiratory Skin Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Mutagenic effects have occurred in experimental animals

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs Central nervous system (CNS), Eyes, Respiratory system, Skin, Liver.

(i) aspiration hazard; Based on available data, the classification criteria are not met

Other Adverse Effects

See actual entry in RTECS for complete information

delayed

Symptoms / effects, both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Do not empty into drains. **Ecotoxicity effects**

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Ethyl ether	10000 mg/L LC50 96 h	EC50 = 165 mg/L/24h		EC50 = 5600 mg/L 15
	2560 mg/L LC50 96 h	_		min

12.2. Persistence and degradability

Persistence Persistence is unlikely, based on information available.

Bioaccumulation is unlikely 12.3. Bioaccumulative potential

Component	log Pow	Bioconcentration factor (BCF)
Ethyl ether	0.82	No data available

12.4. Mobility in soil The product contains volatile organic compounds (VOC) which will evaporate easily from all

surfaces Will likely be mobile in the environment due to its volatility. Disperses rapidly in

12.5. Results of PBT and vPvB

assessment

No data available for assessment.

12.6. Other adverse effects

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

Diethyl ether Revision Date Oct-2018

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives

on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated PackagingDispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalogue, Waste Codes are not product specific, but

application specific.

Other Information Waste codes should be assigned by the user based on the application for which the product

was used. Do not dispose of waste into sewer. Can be incinerated, when in compliance

with local regulations.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN numberUN115514.2. UN proper shipping nameDiethyl ether

14.3. Transport hazard class(es) 3 14.4. Packing group I

ADR

14.1. UN numberUN115514.2. UN proper shipping nameDiethyl ether14.3. Transport hazard class(es)3

14.4. Packing group

<u>IATA</u>

14.1. UN numberUN115514.2. UN proper shipping nameDiethyl ether

14.3. Transport hazard class(es) 3 14.4. Packing group I

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required

14.7. Transport in bulk according to Not applicable, packaged goods

Annex II of MARPOL73/78 and the

IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

Component	EINECS	ELINCS	NLP	TSCA	DSL	NDSL	PICCS	ENCS	IECSC	AICS	KECL
Ethyl ether	200-467-2	-		Χ	Χ	-	Χ	Χ	Χ	Χ	Х

Diethyl ether Revision Date Oct-2018

National Regulations

Component	Germany - Water Classification (VwVwS)	Germany - TA-Luft Class
Ethyl ether	WGK 1	

Component	France - INRS (Tables of occupational diseases)	
Ethyl ether	Tableaux des maladies professionnelles (TMP) - RG 84	

Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment.

Take note of Dir 94/33/EC on the protection of young people at work

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

SECTION 16: OTHER INFORMATION

Full text of R-phrases referred to under sections 2 and 3

R12 - Extremely flammable

R19 - May form explosive peroxides

R22 - Harmful if swallowed

R66 - Repeated exposure may cause skin dryness or cracking

R67 - Vapors may cause drowsiness and dizziness

Full text of H-Statements referred to under sections 2 and 3

H224 - Extremely flammable liquid and vapor

H302 - Harmful if swallowed

H336 - May cause drowsiness or dizziness

EUH019 - May form explosive peroxides

EUH066 - Repeated exposure may cause skin dryness or cracking

Legend

CAS - Chemical Abstracts Service TSCA - United States Toxic Substances Control Act Section 8(b)

Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

No Observed Effect Concentration

Persistent, Bioaccumulative, Toxic

ADR - European Agreement Concerning the International Carriage of

Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime

Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

PNEC - Predicted No Effect Concentration

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% NOEC -

POW - Partition coefficient Octanol:Water PBT -

vPvB - very Persistent, very Bioaccumulative

ICAO/IATA - International Civil Aviation Organization/International Air

Transport Association

MARPOL - International Convention for the Prevention of Pollution from

ATE - Acute Toxicity Estimate

VOC - Volatile Organic Compounds

Diethyl ether Revision Date Oct-2018

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

Creation Date Oct-2013 Next Revision Date Oct-2023

Revision Summary SDS section 1 updated and update of Format

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet